



## Ürün Hakkında

The new Twin Power series offers flexibility and performance like never before. With two gensets under one hood, it ensures backup and reliability twice. Two engines work in synchronization and back2back mode, which ensures a 24/7 power supply. The centralized control and monitoring system enables easy startup and commissioning. It provides savings in terms of total investment and operational costs to the customer.

## Güç

3 Phase, 50 Hz, PF 0.8

Voltaj (V)	STANDBY GÜÇ(ESP)		PRIME GÜÇ (PRP)		STANDBY AKIM (A)
	kW	kVA	kW	kVA	
400 / 231	1184,0	1480	1080,0	1350	2136

STANDBY RATING (ESP) Güvenilir bir şebeke kaynağının güç kesintisi süresince değişken elektrik yüküne güç sağlamak için geçerlidir. ESP, ISO 8528-1'e uygundur. Aşırı yüklemeye izin verilmez.

PRIME RATING (PRP) Değişken elektrik yüküne sınırsız saat boyunca güç sağlamak için geçerlidir. PRP, ISO 8528-1'e uygundur. %10 aşırı yük kapasitesi, 12 saatlik çalışma süresi içinde 1 saatlik bir süre için kullanılabilir.

## Genel Özellikler

Model Adı	AD-TP 1500
Frekans (Hz)	50
Yakıt Tipi	Diesel
Motor Marka ve Modeli	HYUNDAI DP222LB x2
Alternatör Marka ve Modeli	Aksa AK 6540 x2
Kontrol Panel Modeli	InteliGen NT
Kabin Modeli	AK98 - 1500TP

## Motor Özellikleri

### Genel Bilgiler

Üretici	HYUNDAI
Motor Modeli	DP222LB
Silindir Sayısı / Tipi	12 cylinders - V type



Bore mm (in)	128
Stroke mm (in)	142
Hacim I (cu. In)	21.927
Sıkıştırma Oranı	15.0:1
Motor Hızı (rpm)	1500
Standby Güç (kW/hp)	664/903
Prime Güç (kW/hp)	604/821
Blok Isıtıcı (Adt)	1
Blok Isıtıcı Gücü (Watt)	3000
Governor Sistemi	Electronic
Hava Filtresi	Dry Type
Hava Emiş	Turbo Charged and Intercooled (Air to Air)

#### Yağlama Sistemi

Yağ Kapasitesi I (qal)	40
Maks. Yağ Sıcaklığı °C (F)	120

#### Yakıt Sistemi

Yakıt Tipi	Diesel
Enjeksiyon Tipi	Direct
Yakıt Pompa Tipi	WEIFU in-line "P" type

#### Elektrik Sistemi

Çalışma Voltajı (Vdc)	24 Vdc
Akü ve Kapasite (Adt/Ah)	2x143
Şarj Alternatörü (A)	45

#### Soğutma Sistemi

Soğutma Metodu	Water Cooled
Soğutma Suyu Kapasitesi (yalnızca motor)I (gal)	23

#### Egzoz Sistemi

Egzoz Gaz Debisi (m³/dk)	101
Egzoz Geri Basınç in-Hg (kPa)	5.9
Egzoz Gaz Sıcaklığı °C (F)	481
Egzoz Geçen Isı kW (BTU/min)	602

#### Radyatör

Toplam Soğutma Suyu Kapasitesi (l)	104.2
Soğutma Fan Hava Debisi m³/min (ft³/min)	860



Soğutma Havası Harici Direnç (Pa)	125
-----------------------------------	-----

### Yakıt Tüketimi

%100 Prime Yükte Yakıt Tüketimi l/h (kg/h)	147.1
%75 Prime Yükte Yakıt Tüketimi l/h (kg/h)	109.2
%50 Prime Yükte Yakıt Tüketimi l/h (kg/h)	73

### Alternator Özellikleri

Üretici	Aksa
Alternatör Model	AK 6540
Frekans (Hz)	50
Güç (kVA)	675
Voltaj (V)	400
Faz	3
A.V.R.	SX440
Voltaj Regülasyon	1
Yalıtım Sınıfı	H
Koruma Sınıfı	IP22
Nominal Güç Faktörü	0.8
Toplam Generator Ağırlık (kg)	1685
Soğutma Havası (m <sup>3</sup> /dk)	62.1


### Kabin Özellikleri

Uzunluk mm	9000
Genişlik mm	2050
Yükseklik mm	2551
Yakıt Tank Kapasitesi (l)	2000

### Kontrol Paneli

Üretici	Comap
Kontrol Modül Modeli	InteliGen NT
İletişim Portları	MODBUS

1. Start
2. Stop



3. Mode > OFF > MAN > AUT > TEST
4. Fault Reset
5. Mode < OFF < MAN < AUT < TEST
6. Horn Reset
7. GCB control (Open/Close)
8. MCB control (Open/Close)
9. Enter
10. 5% Increase of edited setpoint's value.
11. 5% decrease of edited setpoint's value.
12. Decrease setpoint value.
13. Increase setpoint value.
14. Escape.

### Standart Cihazlar

InteliGen NT Auto Mains Failure control module.  
Static battery charger.  
Emergency stop push button and fuses for control circuits.

### Kontrol Ünitesi

195Vac to 264Vac input voltage range  
45Hz to 440Hz input supply frequency range  
Capability to work direct from 240Vdc to 365Vdc supply voltage  
27.6Vdc factory set DC out-put terminal voltage (option up to 29.4Vdc)  
5.0A dc continuous output current into load  
Capability to work continuously into short-circuit  
Parallel connection for higher output current rating and redundant operation  
Series connection capability for higher output voltage requirements  
No cooling fans are used for high operational reliability  
Aluminum alloy case for robust handling and easy mounting

### Yapım ve Boya

Components installed in a sheet steel enclosure.  
Phosphate chemical, pre-coating of steel provides corrosion resistant surface.  
Polyester composite powder topcoat forms high gloss and an extremely durable finish.  
Lockable hinged panel door provides for easy component access.

### Montaj

Control panel is mounted generating set baseframe on robust steel stand or power module. Located at the side of generating set with proper panel visibility.

### Opsiyonlar

- High oil temperature - Shutdown

### Kontrol Paneli Uyumluluk Listesi



- Low fuel level - Shutdown
- Low fuel level - Alarm
- High fuel level - Alarm
- Customizable load control in parallel with the network
- Wide range of ECU support
- Highly configurable
- Timers, Internal PLC, Force values and more are compatible with ComAp's IntelliVision displays
- Active e-mail messaging and SMS with communication module

EN 60068-2-6 ed.2:2008  
EN 60068-2-27 ed.2:2010  
EN 60068-2-30:2005  
25/55°C, RH 95%, 48hours  
EN 60068-2-64  
EN 61010-1:2003

### Statik Akü Şarj Cihazı

EBC 2405M is designed and optimized for charging all types of Lead Acid batteries (including jell type sealed Lead Acid batteries), protecting the battery and extending its useful lifetime. EBC 2405M can deliver a continuous charging current of 5A into 24V battery system (voltage is set to 27.6Vdc, with an option of up to 29.4Vdc). These battery chargers are designed with performance in mind and special care is taken for protecting and extending the lifetime of the battery.

EBC 2405M is designed with "Switched Mode" technology, where the switching transistor has only two states, ON or OFF, which increases the overall efficiency, hence reducing the excess heat dissipation and in return, increasing the device lifetime and reliability.

The control system is also designed in such a way that; battery is charged in three stages:

Constant current mode (protecting battery cells)

Constant voltage mode (reducing the charge current)

Float charge (compensation of internal self-discharge)

Constant current mode makes sure that; when the battery is drained down below its rated capacity, the high charge current flow into the battery is limited in order to protect the cells and reduce damage to the plates.

As the battery capacity is recovered, each cell voltage reaches up to 2.30Vdc to 2.45Vdc level, which means that the required charging current starts to reduce.

When the required battery terminal voltage is fully reached, the charger keeps supplying just enough current in order to compensate for the internal self-discharge (float charge). This ensures that the battery can maintain its high charge state and deliver its rated output current whenever required.

### Standart Ekipmanlar

- Water cooled, Diesel engine
- Radiator with mechanical fan
- Protective grille for rotating and hot parts
- Electric starter and charge alternator



- Starting battery (with lead acid) including rack and cables
- Automatic synchronising and power control system (Multi gen-set Parallel)
- Engine coolant heater
- Base frame design incorporates an integral fuel tank and anti-vibration isolators
- Flexible fuel connection hoses
- Single bearing, class H alternator
- Industrial exhaust silencer and steel bellows supplied separately(for open sets)
- Static battery charger
- Manual for application and installation

## Opsiyonel Ekipmanlar

### Motor

- Fuel-Water Seperator Filter
- Oil heater

### Kontrol Paneli

- Parallel system with mains
- Transition synchronization with mains
- Alarm output relays
- Earth fault, single set
- Parallel system with mains
- Remote relay output
- Remote communication with modem
- Charge Ammeter

### Yardımcı Ekipmanlar

- Main Fuel Tank
- Automatic or manual fuel filling system
- Electrical or manual oil drain pump
- Low and high fuel level alarm
- Inlet and outlet motorized louvers
- Inlet and outlet acoustic baffles
- Tool kit for maintenance
- 1500/3000 hours maintenance kit
- Supplied with oil and coolant (-30°C)

### Kabin

- Galvanized Coating
- ISO Container
- Marine Grade Paint

## Aksa Sertifikalar

### Direktifler

- 2006/42/EC : Machinery Safety Directive
- 2014/30/EU : Electromagnetic Compatibility Directive
- 2014/35/EU : Low Voltage Directive

### Alternatör

- Anti-Condensation Heater
- Over sized alternator
- PMG excitation + AVR
- Main line circuit breaker

### Transfer Panosu

- Three or four pole contactor
- Three or four pole motor operated circuit breaker

### Egzoz

- Residential Silencer
- Silencer Spark Arrester
- Critical Silencer
- Catalytic Converter

### Opsiyonel Alternatör ve Kontrol Paneli

Please contact to your reseller for additional Alternator, Control Panel and Breaker Switch options.

**Standartlar**

- TS ISO 8528-5:2022 / TS EN ISO 8528-13:2018 : Reciprocating internal combustion engine-driven alternating current generating sets- Part:13: Safety

## Quality Management Systems

ISO 9001:2015  
ISO 14001:2015  
ISO 45001:2018  
ISO 50001:2018  
ISO 27001:2013  
ISO 10002:2018